

Kit 34 gears

Parameters	Hole diameter/mm	Addendum circle diameter/mm	Reference circle diameter/mm	Thickness/mm
8 tooth	1.9	5	4	4.8
10 tooth	1.9	6	5	6
10 tooth	1.9	6	5	9.07
10 tooth	2.4	6	5	5
16 tooth	1.9	9	8	5
20 tooth	1.9	11	10	1.5
double-deck 20/10	1.9	11/6	10/5	1.5/3.5
double-deck 20/10	2	11/6	10/5	1.5/3.5
24 tooth	1.9	13	12	1.5
30 tooth	1.9	16	15	1.5
30 tooth	2.4	16	15	1.5
double-deck 30/10	2	16/6	15/5	1.5+3.5
32 tooth	1.9	17	16	1.5
32 tooth	2.9	17	16	2.5
double-deck 32/10	1.9	6/17	5/16	1.5+3.85
double-deck 32/10	2	17/6	16/5	1.5+3.85
double-deck 32/20	2	17/11	16/10	1.5+3.93
36 tooth	1.9	18	20	1.5
double-deck 46/10	2	23/6	23/5	1.4
48 tooth	1.9	25	24	1.5
48 tooth	2.4	25	24	1.5
56 tooth	1.9	29	28	1.5
80 tooth	1.9	41	40	1.8
120 tooth	1.9	61	60	1.8
Sector 28 tooth	1.9	29	28	1.8
tooth strip	Bore diameter 2.05-2.55mm; 125mm long; 4mm width; 7mm thickness.			
crown	1.9	12.65		2.9+3.85
worm	1.9	diameter 5.9mm; height 9mm.		
worm	1.9	diameter 5.9mm; height 6.75mm.		
belt weel	1.9	ID 4MM	OD 5.4MM	slot width 2
belt weel	1.9	ID 5MM	OD 9MM	slot width 2
belt weel	1.9	ID 13MM	OD 16MM	slot width 2
belt weel	1.9	ID 12.5MM	OD 18MM	slot width 2
belt weel	1.9	ID 21MM	OD 24MM	slot width 2
Tee connector	Through hole DM 2.0 mm, blind hole DM 1.9 mm			
belt (5styles)	After folded length 60, 60, 40, 25, 20mm			